



Infrastructure product

Anybus Wireless Access Point IP67 with Mesh

The Anybus Wireless LAN access points provide you with wireless connectivity at high data rates. Developed for indoor and outdoor industrial settings and with wireless mesh, the Anybus Wireless LAN access points ensure a highly reliable network setup.



FEATURES & BENEFITS

HIGH THROUGHPUT WIRELESS PERFORMANCE

- Concurrent dual-band 2.4 GHz and 5 GHz WLAN, up to 867 Mbit/s + 300 Mbit/s bandwidth
- IEEE 802.11ac Wave 2 compliant, backward compatible with 802.11a/b/g/n

MESH SUPPORT

- Based on Qualcomm® Wi-Fi SON Technology
- Self-healing auto-rerouting through multi-hop (up to 8 hops)

RUGGED DESIGN FOR INDUSTRIAL APPLICATIONS

- Rugged design with IP30 or IP67 classed housing
- Waterproof cable glands for IP67 housing
- Effective heat dissipation design for operations in -40 to 70oC environments
- Support for Power over Ethernet, IEEE 802.3af

ENHANCED SECURITY AND REDUNDANCY

- Firewall for inbound/outbound traffic
- 1:1 NAT, port forwarding for local traffic protection
- Works seamlessly with the Anybus Wireless Bridge and Bolt

CERTIFICATIONS & APPROVALS

Europe	CE
North America	FCC, UL

Ethernet	LAN: 1 x 10/100/1000MBase-T RJ45, auto negotiation, auto-MDI/MDIX WAN: 1 x 10/100/1000MBase-T RJ45, auto negotiation, auto-MDI/MDIX
Antenna connector	2 x N-type female

Operating Temperature	-40 to 70 oC, 5 to 95 % RH non-condensing
WLAN standards	IEEE 802.11ac Wave 2 compliant, backward compatible with 802.11a/b/g/n 2.4 GHz / 5 GHz: 2T2R MU-MIMO DBDC (Dual-band dual-concurrent)
Data rates	802.11ac: MCS 0-9, max. 867 Mbit/s 802.11b: 11Mbit/s, 802.11a/g: 54 Mbit/s, 802.11n: MCS 0-15, max. 300 Mbit/s
Mesh	Qualcomm® Wi-Fi SON Technology
USB	Reserved for future use
Power supply	IEEE 802.3af (48 VDC PoE, Max 11.5W)
Weight	2 400 g
Housing material	Metal
IP class	IP67
Dimensions	269 x 239 x 68 mm without mounting bracket
Mounting	Pole/wall/ mount
Configuration	CGI WebGUI, Command Line Interface (CLI), SNMP, Telnet
Security	TLS v1.2, HTTPs/SSH, First login password management WLAN AP Security: WPA/WPA2-PSK, WPA/WPA2 Enterprise DMZ, IP/Port Filter NAT: 1-1 NAT, NATP(SNAT/DNAT), Port forwarding VPN: IPSec, OpenVPN, L2TP, GRE
Traffic management	Flow control, Traffic shaping
Network management	IPv4, SNMP v1/v2c/v3, DHCP server/client, SysLog, DDNS, DHCP relay, TFTP, SMTP, ARP response over 802.2 LLC SNAP, Proxy ARP, DNS client/proxy
Standards	CE Radio: RED Compliance CE Safety: IEC/EN60950-1, EN 55032, EN55035, EN51000-3-2, EN61000-3-3, EN301489-1/17, EN300328, EN301893, EN300400, N62311MPE FCC part 15B Class A
Product parts included	1 x access point with pole mount AWB5142: 2 x antennas included

File	Version	Size	Read online
------	---------	------	-------------

Ordering Information

Order Code	AWB5142
Included components	Accesspoint
Accessories	AWB4005: PoE Injector 100-240V AWB4006: PoE Injector 12-57V

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.