



## Anybus X-gateway – Ethernet Adapter/Server – J1939

The Anybus X-gateway allows you to monitor and control data on a J1939 heavy duty vehicle network from an Ethernet-based PLC system or device. The EtherNet/IP and Modbus TCP protocols are supported.



### FAST COPYING OF I/O DATA

Data from J1939 messages are mapped to I/O table locations, making them accessible to the Ethernet network. The X-gateway acts as an EtherNet/IP Adapter, allowing J1939 data to be transferred to an EtherNet/IP Scanner device using I/O or explicit messages. The module acts as a Modbus TCP server, allowing J1939 data to be addressed as Modbus registers by a Modbus TCP client device.

### EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

HMS provides the X-gateway with a free Windows based configuration tool (BWConfig). This PC based software allows the user to map J1939 parameter (PGN) data into a range of memory addressable through the X-gateway Ethernet interface.

Configuration of the X-gateway is simple using BWConfig and consists of setting up an I/O table containing selected J1939 PGNs and the rate that each will be read or written from the J1939 network. BWConfig will then automatically map the I/O table to a range of addresses accessible from the X-gateway Ethernet interface.

## Features and benefits

- Monitor and control data on a J1939 heavy duty vehicle network from an Ethernet-based PLC system or device
- Support for EtherNet/IP or Modbus TCP protocols
- Typical applications: Electric Power Generation, Oil & Gas, Marine, Military, Heavy Duty Vehicles, Any Diesel Engine based system supporting J1939
- Max 500 bytes of I/O data in each direction
- Easy configuration via the included BWConfig Windows Software. No programming required
- 10/100 Mbit/s Ethernet adapter interface with IT functionality: HTTP server, FTP server, Telnet server and Email client
- Robust aluminum stand-alone housing
- Global free technical support and consultancy

## Ethernet interface

Ethernet settings can be made either via the included BWConfig Windows Software or for EtherNet/IP, by importing the provided .EDS file into engineering tool of the controlling PLC.

- Supports EtherNet/IP or Modbus TCP protocols
- Supports the EtherNet/IP protocol, Adapter Class with I/O Server, and Message Server
- Supports the Modbus/TCP protocol with up to 8 simultaneous connections and conforms to the Modbus/TCP specification 1.0
- 10/100Mbit operation (auto detect)

- IT Functionality: HTTP server, FTP server, Email client, and a Telnet server.
- IP address settings via DHCP/Bootp, web page, or the Anybus X-gateway Configuration Tool.
- 1x RJ-45 Ethernet port

#### TECHNICAL SPECIFICATIONS

<b>Dimensions (L•W•H)</b>	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
<b>Weight</b>	400g or 0,880 lbs
<b>Operating temperature</b>	-25 to +65 °C or -13 to +149 °F
<b>Storage temperature</b>	-40 to +85 °C or -40 to +185 °F
<b>Power supply</b>	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
<b>Current consumption</b>	max. 400mA (Typical 200mA)
<b>Enclosure material</b>	Aluminium and plastic
<b>Installation position</b>	Vertical / Flat*
<b>Galvanic isolation</b>	YES, on both BUS/Ethernet side
<b>Mechanical rating</b>	IP20, NEMA rating 1
<b>Mounting</b>	DIN-rail (EN 50022 standard)
<b>I/O configuration</b>	via USB port with Anybus Configuration Manager software
<b>Certifications</b>	CE, CULUS, RoHS

File	Version	Size	Read online
------	---------	------	-------------

#### Ordering information

<b>Order Code</b>	AB7665
<b>Included components</b>	Gateway Quick start documentation USB configuration cable Power supply <b>not</b> included Configuration and Anybus OPC server software is available for download.

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.